

Water Quality Report 2013



CITY OF
WATSONVILLE

Why Do We Test Our Drinking Water?

The sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs, and wells. As water travels over the surface of the land or through the ground, it dissolves naturally-occurring minerals and, in some cases, radioactive material, and can pick up substances resulting from the presence of animals or from human activity.

Contaminants that may be present in source water include:

- ♦ **Microbial contaminants**, such as viruses and bacteria, that may come from sewage treatment plants, septic systems, agricultural livestock operations, and wildlife.
- ♦ **Inorganic contaminants**, such as salts and metals, that can be naturally-occurring or result from urban stormwater runoff, industrial or domestic wastewater discharges, oil and gas production, mining, or farming.
- ♦ **Pesticides and herbicides**, that may come from a variety of sources such as agriculture, urban stormwater runoff, and residential uses.
- ♦ **Organic chemical contaminants**, including synthetic and volatile organic chemicals, that are by-products of industrial processes and petroleum production, and can also come from gas stations, urban stormwater runoff, agricultural application, and septic systems.
- ♦ **Radioactive contaminants**, that can be naturally-occurring or be the result of oil and gas production and mining activities.

In order to ensure that tap water is safe to drink, the U.S. Environmental Protection Agency (USEPA) and the California Department of Public Health prescribe regulations that limit the amount of certain contaminants in water provided by public water systems. Department regulations also establish limits for contaminants in bottled water that provide the same protection for public health.

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health effects can be obtained by calling the USEPA's Safe Drinking Water Hotline (1-800-426-4791).



The City of Watsonville is proud to report that the water provided by our Utilities Department met all Federal and State standards for drinking water during 2013.

Information for People with Special Health Concerns

Some people may be more vulnerable to contaminants in drinking water than the general population. Immuno-compromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice

about drinking water from their health care providers. USEPA/Centers for Disease Control (CDC) guidelines on appropriate means to lessen the risk of infection by *Cryptosporidium* and other microbial contaminants are available from the Safe Drinking Water Hotline (1-800-426-4791). Remember, the City's water met all Federal and State standards for drinking water during 2013.

2013 Water Quality Information

This table lists only the substances detected, out of the more than 2,000 water quality analyses conducted during 2013.

Arsenic. While your drinking water meets the federal and state standard for arsenic, it does contain low levels of arsenic. The arsenic standard balances the current understanding of arsenic's possible health effects against the costs of removing arsenic from drinking water. The USEPA continues to research the health effects of low levels of arsenic, which is a mineral known to cause cancer in humans at high concentrations and is linked to other health effects such as skin damage and circulatory problems.

Lead. If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. The City of Watsonville is responsible for providing high quality drinking water, but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at <http://www.epa.gov/safewater/lead>.

Nitrate: Nitrate in drinking water at levels above 45 mg/L is a health risk for infants of less than 6 months of age. Such nitrate levels in drinking water can interfere with the capacity of the infant's blood to carry oxygen, resulting in a serious illness; symptoms include shortness of breath and blueness of the skin. Nitrate levels above 45 mg/L may also affect the ability of the blood to carry oxygen in other individuals, such as pregnant women and those with certain specific enzyme deficiencies.

If you are caring for an infant, or if you are pregnant, you should ask advice from your health care provider. Nitrate levels may rise quickly for short periods of time because of rainfall or agricultural activity. Please note that the City's water did not exceed the State limit for Nitrate in 2013.

Terms & Abbreviations Used in Table:

Public Health Goal (PHG): The level of a contaminant in drinking water below which there is no known or expected risk to health. PHGs are set by the California Environmental Protection Agency.

Maximum Contaminant Level Goal (MCLG): The level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs are set by the U.S. Environmental Protection Agency.

Maximum Contaminant Level (MCL): The highest level of a contaminant that is allowed in drinking water. Primary MCLs are set as close to the PHGs (or MCLGs) as is economically and technologically feasible. Secondary MCLs are set to protect the odor, taste, and appearance of drinking water.

Maximum Residual Disinfectant Level (MRDL): The highest level of a disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary for control of microbial contaminants.

Maximum Residual Disinfectant Level Goal (MRDLG): The level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

Primary Drinking Water Standard (PDWS): MCLs and MRDLs for contaminants that affect health along with their monitoring and reporting requirements.

Regulatory Action Level (AL): The concentration of a contaminant which, when exceeded, triggers treatment or other requirements that a water system must follow.

Treatment Technique (TT): A required process intended to reduce the level of a contaminant in drinking water.

NA: not applicable

ND: not detectable at testing limit

ppb: parts per billion or micrograms per liter

ppm: parts per million or milligrams per liter

pCi/l: picocuries per liter (a measure of radiation)

Source Water Assessment

The Source Water Assessment is a tool to help us protect our water supplies by identifying *potential* sources of contamination. **It is important to note that the City is in compliance with all State water quality regulations.** An assessment of the City's drinking water was completed in March 2013. Our sources are considered most vulnerable to the following activities associated with nitrate detected in the water supply: agricultural drainage channels, fertilizer and pesticide application to irrigated crops. In addition, the sources are considered most vulnerable to gas stations, known contaminant plumes from historical leaking fuel tanks, utility stations, septic systems, and recreational areas.

The City works closely with State agencies to ensure the proper and rapid cleanup of potential contaminant sources, such as leaking underground fuel tank sites, and our program has effectively protected the City water supply. A copy of the complete assessment is available for viewing at the City's Main Library, located at 275 Main Street. A summary of the assessment can be mailed upon request by calling Beau Kayser at 768-3193.

Footnotes to Table

1. The limit of 1,300 ppb for copper & 15 ppb for lead is at the 90th percentile of data after ranking. Lead & copper have not been detected in the City water system, but may occur due to corrosion of plumbing in private homes. Thirty sites were sampled in 2013.

2. The State allows us to monitor for certain contaminants less than once per year because the concentrations of these contaminants do not change frequently. Some of our data, though representative, are more than one year old.

3. Compliance based on presence of coliform bacteria in less than 5% of distribution samples collected in a month.

4. Total trihalomethanes is the sum of chloroform, bromodichloromethane, dibromochloromethane and bromoform.

5. Turbidity is a measure of the cloudiness of the water. We monitor it because it is a good indicator of the effectiveness of our filtration system. Turbidity is measured in NTUs (nephelometric turbidity units).

6. Treatment Technique performance standard: 0.5 NTU for filtered water in 95% of measurements taken each month and shall not exceed 5.0 NTU at any time.

7. Treatment Technique performance standard: 5.0 NTU for unfiltered water at any time.

8. Divide by 17.12 to convert ppm to grains/gallon as CaCO₃.

Primary Drinking Water Standards / Normas primarias del agua potable

SUBSTANCE (UNITS) SUSTANCIA (UNIDAD)	HIGHEST LEVEL ALLOWED: MCL <i>NMC</i>	IDEAL GOALS: PHG OR (MCLG) <i>MSP</i> o (MMNC)	TREATED SURFACE WATER <i>AGUA</i> <i>DE LA SUPERFICIE</i>		TREATED GROUND- WATER ² <i>AGUA</i> <i>SUBTERRÁNEA</i> ²		VIOLATION? ¿VIOLACIÓN?	MAJOR SOURCES <i>ORIGEN</i>
			Range <i>Límites</i>	Average <i>Promedio</i>	Range <i>Límites</i>	Average <i>Promedio</i>		
Arsenic (ppb) <i>Arsénico (ppb)</i>	10	0.004	ND-2.0	1.0	ND-5.7	0.5	No	Naturally occurring mineral <i>Mineral natural</i>
Barium (ppb) <i>Bario (ppb)</i>	1000	2000	ND	ND	3.5-64	32	No	Erosion of deposits of naturally occurring minerals <i>La erosión de depósitos de minerales radioactivas naturales</i>
Chlorine (ppm) <i>Cloro (ppm)</i>	MRDL =4	MRDLG =4	Average= 0.61, Range = 0.24-1.21 <i>Promedio = 0.61, margen = 0.24-1.21</i>				No	Drinking water disinfectant <i>Desinfectante de agua</i>
Chromium (ppb) <i>Cromo (ppb)</i>	50	100	ND	ND	3-23	12.7	No	Naturally occurring mineral; Chrome plating <i>Cromodo; Mineral natural</i>
Total Coliform ³ (% positive) <i>Coliforme total³ (% positivas)</i>	5%	(0)	Highest Monthly % Positive Samples=2% <i>Promedio mensual positivo más alto=2%</i>				No	Naturally present in the environment <i>Existe naturalmente</i>
Copper in tap water (ppb) ¹ <i>Cobre en el agua de beber (ppb)¹</i>	AL=1,300 ¹	170	90 th percentile=1030 ppb; 0 sites exceeded the AL <i>90º percentil=1030 ppb; 0 sitios excedieron el NAR</i>				No	Corrosion of household plumbing <i>Oxidación de la plomería del hogar</i>
Fluoride (ppb) <i>Fluoruro (ppb)</i>	2,000	1,000	210-270	240	60-260	200	No	Naturally occurring mineral <i>Mineral natural</i>
Haloacetic Acids (ppb) <i>Ácidos haloacéticos (ppb)</i>	60	NA	Highest Average = 14.4, Range = 0-20 <i>Promedio más alto = 14.4, margen = 0-20</i>				No	By-product of drinking water chlorination <i>Producto secundario del proceso de cloración</i>
Lead in tap water (ppb) ¹ <i>Plomo en el agua de beber (ppb)¹</i>	AL=15 ¹	0.2	90 th percentile=<2.7 ppb; 0 sites exceeded the AL <i>90º percentil=<2.7 ppb; 0 sitios excedieron el NAR</i>				No	Corrosion of household plumbing <i>Oxidación de la plomería del hogar</i>
Nitrate (ppm as NO ₃) <i>Nitrato (ppm como NO₃)</i>	45	45	0.3-0.7	0.5	0-40.0	6.7	No	Runoff/leaching from fertilizer/septic <i>Escurrimiento/la lixiviación por el fertilizante/ séptico</i>
Total Trihalomethanes ⁴ (ppb) <i>Trihalometano Total⁴ (ppb)</i>	80	NA	Highest Average = 30.2, Range = 2.7-54 <i>Promedio más alto = 30.2, margen = 2.7-54</i>				No	By-product of drinking water chlorination <i>Producto secundario del proceso de cloración</i>
Turbidity (NTU) ⁵ <i>Turbidez (NTU)⁵</i>	TT=0.5 ⁶ TT=5.0 ⁷	NA	100% Com- pliance <i>Complimiento</i>	0.02	Not subject to monitoring <i>No esta sujeto a la obser- vación</i>		No	Eroded Soil in water runoff <i>Tierra que se va con la lluvia</i>
Uranium(pCi/L) <i>Uranio (pCi/L)</i>	20	0.43	ND	ND	ND-1	0.143	No	Erosion of natural deposits <i>Erosion de depositos naturales</i>

Secondary (Non-Health Related) Drinking Water Standards - Aesthetic Qualities that can Affect Taste, Odor & Color ² Secundaria (no relación con la salud) Normas de agua potable - Calidades estéticas que puedan afectar el sabor, olor y color del agua ²

Chloride (ppm) <i>Cloruro (ppm)</i>	500	NA	15-36	26	11-394	49	No	Naturally occurring mineral <i>Mineral natural</i>
Chromium 6 (ppb) <i>Cromo 6 (ppb)</i>	Not regulated <i>No regulado</i>		ND	ND	ND-19	6.4	No	Naturally occurring mineral <i>Mineral natural</i>
Color (Units) <i>Color (unidades)</i>	15	NA	8	8	1-3	1.2	No	Naturally occurring organic materials <i>Materiales organicos naturales</i>
Conductivity (umhos) <i>Conductividad (umhos)</i>	1,600	NA	560-710	635	426-1640	635	No	Naturally occurring mineral <i>Mineral natural</i>
Dissolved Solids (ppm) <i>Sólidos disueltos (ppm)</i>	1,000	NA	350-440	395	226-846	369	No	Naturally occurring mineral <i>Mineral natural</i>
Hardness (ppm) ⁸ <i>Agua dura (ppm)⁸</i>	No limit <i>No límite</i>	NA	240-260	250	189-439	250	No	Naturally occurring mineral <i>Mineral natural</i>
Iron (ppb) <i>Hierro (ppb)</i>	300	NA	ND	ND	ND-290	35	No	Naturally occurring mineral <i>Mineral natural</i>
Manganese (ppb) <i>Manganeso (ppb)</i>	50	NA	ND	ND	ND-31	2.2	No	Naturally occurring mineral <i>Mineral natural</i>
Sodium (ppm) <i>Sodio (ppm)</i>	No Limit <i>No límite</i>	NA	25-54	40	14-140	35	No	Naturally occurring mineral <i>Mineral natural</i>
Sulfate (ppm) <i>Sulfato (ppm)</i>	500	NA	54-56	55	14-97	51	No	Naturally occurring mineral <i>Mineral natural</i>

How We Get Our Water

When rainfall hits the ground in the Pajaro Valley, a portion of the water is absorbed into the ground and eventually reaches the groundwater table. City-owned and private wells then pump the water out for residential, agricultural, and business uses. About 80% of Watsonville's water supply is groundwater, primarily taken from the Aromas Red Sands Aquifer. The remainder is collected from Corralitos and Browns Creeks and treated at a plant in Corralitos.

The City's water meets the strict standards set by the State. However, each year more water is pumped out of the groundwater supplies than is replaced by rainfall. Over-pumping causes saltwater intrusion, the process where ocean water seeps underground into wells, rendering them useless. The City is working with the Pajaro Valley Water Management Agency on water conservation efforts and on projects to increase water supplies in the Pajaro Valley.

While the City of Watsonville uses only 10% of the groundwater pumped in the Pajaro Valley, we must all begin to deal with the challenges created by this shortage. Let's all maintain our precious resources for future generations by continuing to practice water conservation.

¿De dónde proviene el agua potable?

Cuando la lluvia cae en el suelo del Valle del Pájaro, una porción de la lluvia es absorbida por el suelo y ésta a la larga llega al subsuelo. Los pozos municipales y privados bombean el agua para los usos residenciales, agrícolas y comerciales. Cerca del 80% del suministro del agua del subsuelo proviene del acuífero *Aromas Red Sands*. El agua restante proviene de los arroyos Corralitos y el arroyo Browns y pasa por un tratamiento en la planta de filtración de Corralitos.

El agua potable de la Ciudad excede las normas estrictas establecidas por el estado. Sin embargo, hay una escasez de agua en el Valle del Pájaro: cada año se bombea más agua del subsuelo de la que es reemplazada por la lluvia. El bombeo demás causa la intrusión de agua salada (es cuando el agua del océano se filtra por el subsuelo a los pozos convirtiéndolos inservibles y los echa a perder).

Mientras que Watsonville usa solamente el 10% de todo el agua subterránea en el Valle del Pájaro, todos debemos empezar a afrontar los retos ocasionados por la escasez de agua. Hay que mantener nuestros recursos para las generaciones futuras, y así hemos de continuar con el ahorro de agua.

For more information about your water, call Beau Kayser at 768-3193. Additional copies of this report are available at City Hall, or online at www.cityofwatsonville.org/public-works-utilities/water, or call 768-3133. The City Council is the governing body for the City water system. The City Council meets on the second and fourth Tuesday of each month at 4:30 p.m. and 6:30 p.m. in the Council Chambers, 275 Main Street, Fourth Floor. The City welcomes your participation in these meetings.

I ❤️ City of Watsonville Tap Water

The City of Watsonville's tap water is very safe to drink. For your safety, only chlorine is added to the water before distribution, to prevent disease and disinfect the water pipes. Our tap water is not fluoridated. Watsonville's tap water can be trusted more than bottled water as we constantly test our drinking water at the City of Watsonville State-certified Water Quality Lab to ensure quality before it is sent to homes and businesses.

Tap water is also much cheaper! **A family can save \$600-\$1,000 a year by refilling a reusable bottle from the tap!** To improve the taste of tap water, leave an open container out for over half an hour to allow the chlorine taste to disappear, or use a water filter. There's no need to boil water before drinking.

Yo ❤️ el Agua de la Llave de Watsonville

El agua de la llave de Watsonville es muy segura para beber. Para su seguridad, solamente le agregamos cloro antes de ser distribuida, para prevenir enfermedades y desinfectar las tuberías. No le agregamos fluoruro al agua. El agua de la llave de Watsonville es más segura para beber que el agua embotellada, ya que inspeccionamos constantemente el agua en el Laboratorio Certificado de la Ciudad de Watsonville para garantizar su calidad antes de ser distribuida a hogares y negocios.

Además es mucho más barata. **Una familia puede ahorrar \$600-\$1,000 al año llenando una botella reusable con agua de la llave.** Para mejorar el sabor, deje reposar el agua en un contenedor abierto por más de media hora para que el sabor a cloro desaparezca, o use un filtro. No es necesario hervir el agua antes de tomarla.

Drink Watsonville Tap Water!
Healthy and Safe!



¡Beba Agua de la Llave de
Watsonville! ¡Segura y Saludable

Reporte de la calidad del agua del 2013



La Ciudad de Watsonville está orgullosa de informarle que el agua suministrada por nuestro Departamento de Utilidades cumplió con todas las normas federales y estatales para el agua potable durante 2013.

Información para Personas con Problemas de Salud

Algunas personas pueden ser más susceptibles a los contaminantes en el agua potable que la población en general. Por ejemplo, las más susceptibles a infecciones son aquellas con un sistema inmune delicado, incluso las personas con cáncer y en tratamiento de quimioterapia, las personas que se les hizo un trasplante de un órgano, las personas con VIH o SIDA o algún otro problema médico del sistema inmune, algunas personas ancianas y bebés.

Estas personas deben consultar con su médico si tienen dudas. Usted puede obtener las normas para reducir el peligro de infección por *Cryptosporidium* u otros contaminantes microbianos de la USEPA y el Centro para el Control de Enfermedades (sus siglas en inglés CDC) llamando a la Línea Telefónica de Agua Potable al (800-426-4791). Recuerde que el agua de la Ciudad cumplió con todas las normas federales y estatales para el año 2013.

¿Por qué analizamos el agua potable?

Las fuentes de agua potable (tanto el agua corriente como el agua embotellada) incluyen ríos, lagos, arroyos, lagunas, reservorios, manantiales y pozos. Al correr el agua sobre la superficie de la tierra o por debajo del suelo, disuelve los minerales presentes naturalmente y puede arrastrar sustancias originadas por la presencia de animales o de la actividad humana. Los agentes contaminantes que pueden encontrarse en el agua antes del tratamiento de ésta, incluyen:

- ♦ **Agentes contaminantes microbianos**, como virus y bacterias, que pueden provenir de plantas depuradoras de aguas residuales, sistemas sépticos, operaciones agropecuarias, y fauna y flora silvestre.
- ♦ **Agentes contaminantes inorgánicos**, como sales y metales, que pueden estar presentes naturalmente o pueden surgir como consecuencia de la escorrentía pluvial de las zonas urbanas, descargas de aguas residuales industriales o domésticas, producción de petróleo y gas, y actividades de minería o agricultura.
- ♦ **Pesticidas y herbicidas**, que pueden provenir de diversas fuentes, por ejemplo, agricultura, escorrentía pluvial de las zonas urbanas y usos residenciales.
- ♦ **Agentes contaminantes químicos orgánicos**, incluidos productos químicos orgánicos sintéticos y volátiles, que son subproductos de procesos industriales y de la producción petrolera, y también pueden provenir de estaciones de servicio, escorrentía pluvial de las zonas urbanas, uso agrícola y sistemas sépticos.
- ♦ **Agentes contaminantes radiactivos**, que pueden estar presentes naturalmente o que pueden surgir como resultado de la producción de petróleo y gas, y actividades de minería.

Para garantizar que el agua corriente sea saludable para el consumo, la Agencia de Protección Ambiental de los EE. UU. (U.S. Environmental Protection Agency, USEPA) y el Departamento de Salud Pública de California (California Department of Public Health) prescriben reglamentaciones que limitan la cantidad de ciertos agentes contaminantes en el agua suministrada por los sistemas públicos de abastecimiento de agua. Las regulaciones estatales también establecen límites para los agentes contaminantes del agua embotellada ya que deberán proveer el mismo nivel de protección a la salud pública.

Es razonable que el agua potable, incluso la embotellada, contenga por lo menos cantidades pequeñas de algunos contaminantes. La presencia de contaminantes no significa un peligro para la salud. Puede obtener más información tocante los contaminantes y los posibles efectos a la salud llamando a la Línea Telefónica de Agua Potable de la USEPA al (1-800-426-4791).

Para recibir más información sobre el agua potable, llame a Beau Kayser al 768-3193. Las copias adicionales de este informe están disponibles en las oficinas municipales o llamando al 768-3133 o en línea a www.cityofwatsonville.org/public-works-utilities/water. El Concilio Municipal es el cuerpo legislativo del sistema del agua potable de la Ciudad. El Concilio Municipal se reúne el segundo y cuarto martes de cada mes a las 4:30 p.m. y 6:30 p.m. en la Cámara del Concilio, ubicada en 275 Main Street, cuarto piso. La Ciudad les invita a que asistan a estas juntas.

Información de la calidad del agua del 2013

Esta tabla enumera las sustancias detectadas de las mas que 2,000 muestras que se efectuaron durante el año 2013.

Arsénico. Aunque el agua potable cumple con las normas federales y estatales de arsénico, ésta contiene niveles bajos de arsénico. Las normas buscan un equilibrio entre lo que se conoce hasta ahora sobre los efectos posibles del arsénico en la salud y los costos de remover el arsénico del agua potable. USEPA continua con las investigaciones de los niveles bajos del arsénico en la salud, el cual es un mineral conocido como causante de cáncer en altas concentraciones y se vincula con otros efectos a la salud tales como daños a la piel y problemas circulatorios.

Plomo. Si está presente, el plomo en niveles elevados puede causar problemas serios a la salud, especialmente a mujeres embarazadas y niños pequeños. El plomo que se encuentra en el agua potable proviene de la tubería y plomería de su casa. La Ciudad de Watsonville es responsable por proveer agua potable de la más alta calidad, pero no puede controlar la variedad de materiales que se utilizan en la plomería. Si no habré las llaves de su casa por varias horas, puede minimizar el riesgo de exponerse al plomo dejando correr el agua entre 30 segundos a 2 minutos antes de tomar o usar el agua para cocinar. Si está preocupado por el nivel de plomo en su agua puede hacer una prueba. Para información sobre el plomo en el agua potable, tipos de pruebas disponibles, y sugerencias en cómo minimizar su exposición hable a Safe Drinking Water Hotline (línea telefónica de agua potable segura) o visite el sitio <http://www.epa.gov/safewater/lead>.

Nitratos: El nitrato en el agua potable a un nivel de más de 45 mg/L es un riesgo para la salud en los niños menores de 6 meses de edad. Tales niveles de nitrato en el agua potable puede interferir con la capacidad de la sangre de portar el oxígeno, que resultaría que la piel se pusiera azul. Los niveles de nitrato de más de 45 mg/L pueden también afectar la habilidad de la sangre de portar el oxígeno en otros individuos, así como las mujeres embarazadas y aquellos con ciertas deficiencias de enzimas específicas. Si está cuidando a un niño o si esta embarazada, debe consultar su proveedor de cuidado de salud. Los niveles de nitrato pueden subir rápidamente por intervalos cortos de tiempo a causa de la lluvia o la actividad agrícola. **Note que el nivel del nitrato del agua en 2013 no sobrepasó el límite establecido por el estado.**

Términos y abreviaciones usadas en la tabla a la izquierda

Meta de la Salud Pública (MSP): El nivel más bajo de un contaminante en el agua potable bajo el cual no se conoce o se espera que haya peligro a la salud. El MSP se calcula por la Agencia de la Protección del Medio Ambiente de California.

Meta Máxima Del Nivel de Contaminación (MMNC): El nivel más bajo de un contaminante en el agua potable bajo el cual no se conoce o se espera que haya peligro a la salud. El MMNC es calculado por la Agencia de la Protección del Medio Ambiente.

Nivel Máximo de Contaminación (NMC): El nivel más alto de un contaminante que se permite en el agua potable. El NMC primario se establece lo más cerca de los MSP's (o MMNC's) como sea práctico económicamente y tecnológicamente. Los MCLs secundarios se establecieron para proteger el olor, sabor y apariencia del agua.

Nivel máximo de desinfectante residual (MRDL): El nivel más alto de desinfectante permitido en el agua potable. Existe evidencia que indica que es necesario añadir un desinfectante para el control de contaminantes microbianos.

Meta para nivel máximo de desinfectante re-

sidual (MRDLG): El nivel de desinfectante de agua potable por debajo de la cantidad que no se reconoce o se espera riesgo alguno para la salud. Los estándares de MRDLGs no reflejan los beneficios del uso de desinfectantes para el control de contaminantes microbianos.

Norma Primaria del Agua Potable (NPAP): NMC para los contaminantes que afectan la salud junto con los requisitos en materia de informes e inspecciones.

Nivel de Acción Reglamentaria (NAR): La concentración de un contaminante, que cuando es excedida, causa que se efectúen tratamientos u otros requerimientos al sistema del agua.

Técnica de Tratamiento (TT): Un proceso que es requerido con el propósito de reducir el nivel de un contaminante en el agua potable.

NA: no es pertinente

ND: no es detectable

ppb: partes por mil millones o microgramos por litro

ppm: partes por millón o miligramos por litro

pCi/l: una medida de radiación

La Evaluación Fuentes del Agua

La Evaluación Fuentes del Agua es un instrumento utilizado para identificar potenciales de contaminación en nuestros suministros de agua potable. **Es muy importante señalar que la Ciudad de Watsonville cumple con todos las leyes establecidas para la provisión de agua potable del Estado de California.** Durante de marzo del 2013 se desarrollo una evaluación sobre el sistema de agua potable de la Ciudad. La evaluación concluyo que nuestras fuentes de agua son vulnerables a las actividades relacionadas con nitratos, tales como: canales de desagüe agrícola, fertilizantes y aplicar pesticidas en cultivos de riego. Asimismo, nuestras fuentes de agua son más vulnerables a gasolineras, tanques de combustible que históricamente han demostrado fugas de gases contaminantes, instalaciones de empresas de servicios públicos, fosas sépticas, e áreas recreativas.

La Ciudad trabaja conjuntamente con las agencias del Estado para garantizar que se toman las medidas adecuadas y rápidas para la limpieza de las posibles fuentes de contaminantes tales como terrenos donde existen tanques subterráneos con fugas. Consecuentemente, nuestro programa ha protegido muy eficazmente las fuentes de agua municipal. Puede encontrar una copia de la evaluación total en la Biblioteca Principal de la Ciudad, ubicada en el 275 de la calle Main Street. Si gusta puede solicitar una copia del resumen de la evaluación por correo comunicándose con Beau Kayser a 768-3193.

Notas al pie de la tabla

1. El límite de 1,300 ppb (cobre) & 15 ppb (plomo) están en el 90^{avo} percentil después de clasificar la información. El cobre y plomo no se han detectado en los sistemas de agua, pero pudiera ocurrir a causa de la oxidación de la plomería de las casas. En 2013 se tomaron muestras de 30 lugares.
2. El Estado nos permite monitorear ciertos contaminantes menos de una vez por año porque las concentraciones de estos contaminantes no cambian con frecuencia. Algunos de nuestros datos, aunque representativa, tienen más de un año.
3. El acatamiento basado en la presencia de la bacteria de coliforme debe ser menos del 5% de la distribución de las muestras colectadas en un mes.
4. El total de los trihalometanos son la suma de cloroformo, bromodichlorometano, dibromochlorometano y bromoform.
5. Turbidez es la medida de la nubedad del agua. La monitoreamos ya que es un buen indicador de la eficacia de nuestro sistema de filtración. La turbidez se mide en unidades de turbidez nefelométricas (UTN).
6. La Norma de Cumplimiento de la Técnica de Tratamiento: 0.5 UTN en el agua filtrada en 95% de las medidas que se examinan cada mes y no deberá en ningún tiempo exceder el 5.0 UTN.
7. La Norma de Cumplimiento de la Técnica de Tratamiento: 5.0 UTN para agua que no ha sido filtrada nunca.
8. Dividir por 17.12 para convertir ppm a los granos como CaCO₃.